

Cyclone

Fast Blow Apply Label Applicator

Fast blow apply label applicator for flash and promotional label application.

Cyclone is a fast blow apply label applicator designed for accurate flash and promotional label application, available as a single or twin applicator (as shown in image). The 360 degree head rotation enables any orientation of label placement and at an impressive speed of up to 150 labels per minute this non-contact applicator is ideal for a range of products.

Options:

Single or Twin Cyclone Applicators with or without conveyor



Technical Specification (Fully refurbished 2nd user)

Application Method	Blow Apply label applicator
Materials	Stainless Steel, anodised aluminium and food grade plastics
Features	Lift and traverse mechanism, rotation through 360 degrees
Label Specification	Width 30mm to 100mm / Length 30mm to 150mm
Label Reel	Core diameter 76mm / Outside diameter 300mm / Inside or outside wound (Outside as standard)
Placement Accuracy	Typically +/- 1mm depending on external criteria
Pack sizes	Length up to 650mm / Width up to 250mm / Height up to 150mm
Speed	Up to 150 ppm dependent on pack and label characteristics and feed conditions
Conveyor Length	Single - 1000mm / Twin - 1500mm
Conveyor Width	225mm / Maximum carrying weight 10kg / Adjustable speed
Services	Power: Standard 230v, 50/60Hz / Air: 5 bar clean dry air



Tel: 01440 765 380

Email: info@sureservice.co.uk

www.sureservice.co.uk

Brocks Business Centre, Homefield Road, Haverhill, Suffolk CB9 8QP